#### **NOTICE 390 OF 2015**

### INDEPENDENT COMMUNICATIONS AUTHORITY OF SOUTH AFRICA



Radio Frequency Spectrum Assignment Plans for International Mobile Telecommunications (IMT)

NOTICE REGARDING THE ERRATUM TO THE FINAL RADIO FREQUENCY SPECTRUM ASSIGNMENT PLAN FOR THE FREQUENCY BAND 791 TO 821 MHz AND 832 TO 862 MHz.

The Independent Communications Authority of South Africa hereby issues an erratum notice to the published Radio Frequency Spectrum Assignment Plan dated 30 March 2015 (Notice No. 273 of 2015) to the extent reflected in the schedule.

The purpose of the erratum is to give clarity with regard to the relationship between the implementation date and the transitional arrangements and to also correct typographical errors.

Dr SS MNCUBE CHAIRPERSON

### **SCHEDULE**

# 1. Substitution of paragraphs 6.1 and 6.2:

- "6.1 The Radio Frequency Assignment Plan comes into effect on the 1st July 2015 subject to the Transitional Arrangements in paragraph 9.
- 6.2 The process of assignment may commence prior to the date referred to in paragraph 6.1."

# 2. Substitution of paragraph 7.2:

"7.2 The following field strength thresholds have to be assured based on (ECC/REC(11)04 for 790-862MHz. Operator-to-operator coordination may be necessary to avoid interference.

In general stations of FDD systems may be used without coordination with a neighboring country if the mean field strength produced by the cell (all transmitters within the sector) does not exceed the value of  $55 dB\mu V/m/5MHz$  at a height of 3m above ground at the borderline between countries and does not exceed a value of  $29 dB\mu V/m/5MHz$  at a height of 3m above ground at a distance of 9 km inside the neighboring country.

In the case that LTE is deployed both sides of the border the field strength levels can be increased to 59 dB $\mu$ V/m/5MHz and 41 dB $\mu$ V/m/5MHz at 6 km.

If TDD is in operation across both sides of a border and is synchronised across the border then field strength levels such as those in Annex 1 may be applicable. Field strength levels should be agreed on a bilateral basis.

For field strength predictions the calculations should be made according to Appendix B. In cases of other frequency block sizes 10\*log (frequency block size/5MHz) should be added to the field strength values e.g.:

BW (MHz)	Field strength level at 3 m height	Field strength level at 3 m height
	(general case)	(LTE case)
5 MHz	55.0 dBμV/m/5MHz @0km	59.0 dBμV/m/5MHz @0km
	29.0 dBμV/m/5MHz @9km	41.0 dBμV/m/5MHz @6km
10 MHz	58.0 dBμV/m/10MHz @0km	62.0 dBμV/m/10MHz @0km

	$32.0~\text{dB}\mu\text{V/m}/10\text{MHz}$ @9km	44.0 dBµV/m/10MHz @6km
15 MHz	59.8 dBμV/m/15MHz @0km	63.8 dBμV/m/15MHz @0km
	33.8 dBµV/m/15MHz @9km	45.8 dBµV/m/15MHz @6km
20 MHz	61.0 dBµV/m/20MHz @0km	65.0 dBµV/m/20MHz @0km
	35.0 dBµV/m/20MHz @9km	47.0 dBµV/m/20MHz @6km

If neighboring administrations wish to agree on frequency coordination based on preferential frequencies, while ensuring a fair treatment of different operators within a country the Authority will add these within mutual agreements.

Stations of IMT systems may be operated without coordination if the mean field strength produced by the cell (all transmitters within the sector) does not exceed the value of  $15dB\mu V/m/5$  MHz at 10% time, 50% of locations at 3 metres above ground level at the borderline."

# 3. Addition of paragraph 9.3:

"9.3 Sharing and co-existence in this band is to be implemented systematically through a Geographic separation of Mobile IMT Systems and Broadcasting Services in affected areas in accordance with the Terrestrial Broadcasting Frequency Plan 2013, Government Gazette 36321read with the First Update to the Terrestrial Broadcasting Plan 2013 Government Gazette 38005<sup>[1]</sup> until the end of migration from Analogue to Digital Terrestrial Television process."

### **End of erratum**

<sup>&</sup>lt;sup>[1]</sup> The Multiplexes in the latest updated version of the terrestrial Broadcasting Plan 2013 has been coordinated in terms of the GE06 Agreement and meets the conformance requirements of the Plan. The frequencies 694 MHz on this version have been successfully notified to the ITU-R Bureau and have been included in the Master International Frequency Register.